

MSR 255 datalogger

Robust multi-talent with LCD screen



MSR 255 with ext. sensors



With up to five different sensors, four additional analogue inputs and an easy to read LCD screen the compact MSR 255 offers maximum possible flexibility and user-friendliness.

The measuring tasks undertaken by the user define the way in which the MSR255 is configured: There is a choice of temperature, humidity, air pressure and light sensors (fitted internally within the case or externally on a cable) together with a sensor for measuring acceleration in all three co-ordinate axes. The 3-axis acceleration sensor allows the peak value to be recorded once a second whilst making measurements of up to 1600 values per second per axis. In addition, the voltage of four further external analogue channels or sensors can also be recorded. The analogue inputs feature an alarm output, multiple output switching power supply and an input for starting and stopping data recording.

The memory capacity of the MSR255 is over 2 million measurement parameters. Thanks to its high-capacity lithium polymer battery the datalogger is ideal for long term data acquisition applications. The 4-row backlit LCD display has four individually configurable views. All acquired data can be quickly transferred to a PC or laptop via the USB interface



Technical data for the MSR 255

Housing:	Anodised aluminium industrial case (standard IP60, optional IP67 protection class), top-hat tail snapper (TS 35)
Size & weight:	78 x 62 x 38 mm, approx. 222g
Operation:	Two keys for selecting functions and controlling data recording
Display:	Four row LCD matrix display
LED:	3 colour LED to indicate data recording, alarm and charge condition
Integrated sensor:	Selection of different sensors for temperature, relative humidity, pressure, light and 3-axis acceleration/position
Measurement rate (MR):	1/s to every 12h (acceleration up to 1600/s)
Storage rate (SR):	1/s to every 12h
Power supply:	Rechargeable lithium polymer battery 2300 mAh
PC software:	Free Setup, Reader, Viewer- & Online software (Windows 2000/XP/Vista/7)
Interface:	USB (Mini-B)
Operating conditions:	Temperature -20°C to +65°C
Storage conditions:	Temperature +5°C to +45°C (ideal storage condition for the battery) 0-95% relative humidity, non-condensing
Standard:	The MSR 255 complies with EU-Directive RoHS/WEEE

Caption Data Limited
Unit 8 Brindley Court
Gresley Road
Worcester
WR4 9FD

Tel: 01905 754078
Fax: 01905 759640

Email: enquiries@captiondata.com
www: www.captiondata.com

MSR 255 datalogger

Robust multi-talent with LCD screen

Measurement parameters for the sensors (internal and external)

Your MSR 255 datalogger can be fitted with up to five different sensors. If required, you may select from the following external sensors in place of the corresponding internal ones: temperature, relative humidity, air pressure and light. The available cable lengths are: 0.15m, 0.40m, 1.00m and 1.60m.

Measured parameters	Working range	Accuracy	Measurement/storage rate
Temperature	int.: -20°C to +65 °C ext: -55°C to +125°C	±0.5°C (-10°C-+65°C) ±2°C (-55°C-+125°C)	1/s to every 12h
Relative humidity with integrated temperature	0-100% rel. humidity -20°C to +65°C	±2% rel. humidity (10-85% rel. humidity, 0°C to +40°C) ±4% rel. humidity (85-95% rel. humidity, 0°C to +40°C)	1/s to every 12h
Air Pressure Absolute, with integrated temperature	0-2000 mbar absolute -20°C to +65°C	±2.5 mbar (750-1100 mbar absolute, +25°C)	1/s to every 12h
	optional: 0-14 bar absolute -20°C to +65°C	±50 mbar (1-10 bar absolute, +25°C)	1/s to every 12h
3-axis acceleration (peak value detection/fast peak)	±15g	±0.15g (+25°C)	MR: 1600/s SR 1/s to every 12h
Light	0-65000 lx	Max. sensitivity at 500 nm	1/s to every 12h

Additional analogue inputs for connecting third-party sensors

It is possible to expand the range of possible applications for which your MSR255 can be used by specifying four analogue inputs. These additional inputs allow external sensors for a wide range of measuring tasks to be connected. If required, these third-party sensors can be powered by the logger's internal battery. The power can be automatically turned on before measurements take

MSR 255 with 4 analogue inputs	Technical data
Including an alarm output, multiple output switching power supply and an input for starting and stopping data recording.	4 analogue inputs with freely selecta-ble input configuration: 0...20 mA; 4...20 mA; 0...3.0 V; 0.5...4.5 V; 0...5.0 V; 1.0...6.0 V; 0...10.0 V; 0...12.0 V; 0...24.0 V Resolution: 12 Bit Measurement/storage rate: 1/s to every 12 h

Its flexibility makes the autonomous MSR255 datalogger ideally suited for the most diverse documentation and monitoring applications in industry and science. Modular Signal Recorder

Configure your ideal MSR 255 today – We will be pleased to provide you with prices and terms of delivery

Options



External Temperature Sensor



External Humidity Sensor



External Air Pressure Sensor

Caption Data Limited
Unit 8 Brindley Court
Gresley Road
Worcester
WR4 9FD

Tel: 01905 754078
Fax: 01905 759640

Email: enquiries@captiondata.com
www: www.captiondata.com